

```

$TTL      604800
@         IN      SOA      a22702.a227.cis. hostmaster.a22702.a227.cis. (
                2013061301      ; Serial
                604800      ; Refresh
                86400      ; Retry
                2419200     ; Expire
                604800 )     ; Negative Cache TTL
;
@         IN      NS       ns.a22702.a227.cis.
1         IN      PTR      ns.a22702.a227.cis.

25        IN      PTR      dhcp25.a22702.a227.cis.
26        IN      PTR      dhcp26.a22702.a227.cis.
27        IN      PTR      dhcp27.a22702.a227.cis.
28        IN      PTR      dhcp28.a22702.a227.cis.
29        IN      PTR      dhcp29.a22702.a227.cis.
30        IN      PTR      dhcp30.a22702.a227.cis.

```

File: /home/pima30713/bind/named.conf.local

```

//
// Do any local configuration here
//
// Consider adding the 1918 zones here, if they are not used in your
// organization
//include "/etc/bind/zones.rfc1918";

zone "a22702.a227.cis" {
    type master;
    file "/etc/bind/db.a22702.a227.cis";
};

zone "2.27.172.in-addr.arpa" {
    type master;
    file "/etc/bind/db.2.27.172";
};

```

File: /home/pima30713/bind/db.a22702.a227.cis

```

$TTL      604800
@         IN      SOA      a22702.a227.cis. hostmaster.a22702.a227.cis. (
                2013061301      ; Serial
                604800      ; Refresh
                86400      ; Retry
                2419200     ; Expire
                604800 )     ; Negative Cache TTL
;
@         IN      NS       ns.a22702.a227.cis.
@         IN      A        172.27.2.1
ns        IN      A        172.27.2.1

dhcp25    IN      A        172.27.2.25
dhcp26    IN      A        172.27.2.26
dhcp27    IN      A        172.27.2.27
dhcp28    IN      A        172.27.2.28
dhcp29    IN      A        172.27.2.29
dhcp30    IN      A        172.27.2.30

```